

DESCRIPTION

Helps to prevent the bonding of snow and ice to pavements when used before snow falls. This pre-treatment will accelerate the action of solid ice melt products that are applied after Snow Away. Can also be used on outdoor mechanical handling systems such as conveyors and elevators, as well as on walkways, rail switches and virtually all outdoor deicing applications.

DISPOSAL

Offer empty container for recycling. If recycling is not available, discard container in trash.

TOTAL SOLUTIONS®

WINTER PRODUCTS

SNOW AWAY

- FAST AND EASY TO USE
- LOWERS OPERATING TEMPERATURES OF SOLID ICE MELT PRODUCTS
- IMPROVES PERFORMANCE AND LONGEVITY OF SOLID ROCK SALT AND SAND WHEN APPLIED PRIOR TO THEIR USE
- FOR USE ON PARKING LOTS, ROADWAYS, SIDEWALKS, OR OTHER FOOT TRAFFIC AREAS
- EFFECTIVE IN TEMPERATURES OF -10°F

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS:

□5 □6 □30 □35 □55 Gallons

Manufactured By: Total Solutions®
PO Box 240014 • Milwaukee, WI 53224
1-800-743-6417

DIRECTIONS:

USAGE AND APPLICATION RATES:

1) **ACCELERATOR** - Significantly improves the performance and longevity of solid rock salt and abrasives like sand. Application: 0.5 Gallons/1000 square feet. Adjust dilution depending on requirement.

2) **ANTI-ICER/PRE-WETTER** - Spray on pavement before precipitation begins. Application: 0.5 Gallons/ 1000 square feet. Adjust dilution depending on requirement.

3) **DEICER** - Effective deicer when applied on top of snow and ice. On glazed ice it may be necessary to score the surface in several places before applying to allow penetration and to prevent run-off. More than one application may be necessary in extreme conditions.

Recommended Application: Near 32° F on thin ice use 1.0 - 2.0 gallons/1000 square feet. Less than 10° F use 3.0 - 6.0 gallons/1000 square feet.

DILUTION RATIO

TEMPERATURE	PRODUCT	WATER
-10° F	1	0
0° F	3	1
+10° F	2	1
+20° F	1	1

As with all deicers, use only on properly placed and cured concrete. Do not use on porous or improperly cured concrete or concrete less than one year old. The cycle of freezing and thawing by natural weather elements can cause damage to concrete. The use of an ice melt increases these cycles and are factors over which we have no control. Use of deicers on porous brick, mortar joints, flagstone and pre-cast or pre-stressed concrete is not recommended. All deicers can be harmful when applied directly to trees, shrubs, flower beds or grass. Remove any melted ice, snow and slush from vegetation area. Ice melting agents that are applied at much greater rates than recommended may interfere with tracking or footing, and may cause tracking indoors. Use of this ice melter is at the consumer's risk.

NFPA® RATINGS

Health: 1; Flammability: 0; Reactivity: 0

CONTAINS/CAS NUMBER: Water/7732-18-5; Sodium Chloride/7647-14-5; Yellow Prussiate of Soda/13601-19-9



Please Recycle.

For industrial and commercial use only.
For additional information, see Safety Data Sheet.

0286.082715