

SECTION 1: Product and company identification

Product name : Grease Cutter
 Use of the substance/mixture : Cleaner
 Product code : 0426
 Company : Total Solutions
 P.O. Box 240014
 Milwaukee, WI 53224 - USA
 T (414) 354-6417
 Emergency number : Chemtec: (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Met. Corr. 1 H290
 Skin Corr. 1C H314

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS05

Signal word (GHS-US) : Danger
 Hazard statements (GHS-US) : May be corrosive to metals
 Causes severe skin burns and eye damage
 Precautionary statements (GHS-US) : Keep only in original container
 Do not breathe mist, spray
 Wash thoroughly after handling
 Wear eye protection, protective clothing, protective gloves
 If swallowed: rinse mouth. Do NOT induce vomiting
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
 If inhaled: Remove person to fresh air and keep comfortable for breathing
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 Immediately call a doctor, a POISON CENTER
 Specific treatment (see First aid measures on this label)
 Wash contaminated clothing before reuse
 Absorb spillage to prevent material damage
 Store locked up
 Store in corrosive resistant container with a resistant inner liner
 Dispose of contents/container to comply with local/regional/national/international regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

Full text of H-phrases: see section 16

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Glycol Ether EB	(CAS-No.) 111-76-2	3-7	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Asp. Tox. 1, H304
potassium hydroxide	(CAS-No.) 1310-58-3	3-7	Met. Corr. 1, H290 Acute Tox. 3 (Oral), H301 Skin Corr. 1A, H314
Sodium Tripolyphosphate Anhydrous	(CAS-No.) 7758-29-4	3-7	Not classified

Grease Cutter

Safety Data Sheet

TOTAL
SOLUTIONS™

Name	Product identifier	%	GHS-US classification
Sodium xylene sulphonate	(CAS-No.) 1300-72-7	1-5	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
sodium dodecylbenzenesulfonate	(CAS-No.) 25155-30-0	1-5	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335
Cocamidopropyl Hydroxy Sultaine	(CAS-No.) 68139-30-0	1-5	Skin Irrit. 2, H315 Eye Irrit. 2A, H319
2-aminoethanol, ethanolamine	(CAS-No.) 141-43-5	0.5-1.5	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1B, H314 STOT SE 3, H335

A specific chemical identity and/or percentage of composition has been withheld as a trade secret. Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : If you feel unwell, seek medical advice (show the label where possible). IF exposed or concerned: Get medical advice/attention.
- First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- First-aid measures after skin contact : Take off immediately all contaminated clothing and wash it before reuse. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects : Causes severe skin burns and eye damage.
- Symptoms/effects after inhalation : May cause respiratory irritation.
- Symptoms/effects after skin contact : Causes severe burns.
- Symptoms/effects after eye contact : Causes serious eye damage. Corrosion of the eye tissue. Permanent eye damage.
- Symptoms/effects after ingestion : Gastrointestinal complaints. Burns to the gastric/intestinal mucosa.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Adapt extinguishing media to the environment.

5.2. Special hazards arising from the substance or mixture

- Reactivity : Upon combustion: CO and CO₂ are formed.

5.3. Advice for firefighters

- Firefighting instructions : Exercise caution when fighting any chemical fire. Use water moderately and if possible collect or contain it. Use water spray or fog for cooling exposed containers.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Isolate from fire, if possible, without unnecessary risk.

6.1.1. For non-emergency personnel

- Protective equipment : Gloves. Protective goggles. Protective clothing.
- Emergency procedures : Evacuate unnecessary personnel. Avoid contact with skin, eyes and clothing. Ventilate spillage area.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Stop leak if safe to do so. Stop release. Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent soil and water pollution.

6.3. Methods and material for containment and cleaning up

- For containment : Contain released substance, pump into suitable containers.

Grease Cutter

Safety Data Sheet

Methods for cleaning up : This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Comply with the legal requirements. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Do not get in eyes, on skin, or on clothing.

Hygiene measures : Wash thoroughly after handling. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations. Always add the product to the water for dilution/mixture. Never add water to this product.

Storage conditions : Keep container closed when not in use. Store in original container. Store in corrosive resistant container with a resistant inner liner.

Incompatible products : Strong acids. aluminum. Tin. zinc.

Incompatible materials : Cleaning agent.

Information on mixed storage : KEEP SUBSTANCE AWAY FROM: (strong) acids.

Storage area : Store in a dry area. Store in a cool area. Keep locked up.

Special rules on packaging : meet the legal requirements.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Glycol Ether EB (111-76-2)		
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	Remark (ACGIH)	Eye & URT irr
OSHA	OSHA PEL (TWA) (mg/m³)	240 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	50 ppm
potassium hydroxide (1310-58-3)		
ACGIH	ACGIH Ceiling (mg/m³)	2 mg/m³
ACGIH	Remark (ACGIH)	URT, eye, & skin irr
Sodium Tripolyphosphate Anhydrous (7758-29-4)		
Not applicable		
Sodium xylene sulphonate (1300-72-7)		
Not applicable		
2-aminoethanol, ethanolamine (141-43-5)		
ACGIH	ACGIH TWA (ppm)	3 ppm
ACGIH	ACGIH STEL (ppm)	6 ppm
ACGIH	Remark (ACGIH)	Eye & skin irr
OSHA	OSHA PEL (TWA) (mg/m³)	6 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	3 ppm
Cocamidopropyl Hydroxy Sultaine (68139-30-0)		
Not applicable		
sodium dodecylbenzenesulfonate (25155-30-0)		
Not applicable		

8.2. Exposure controls

Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Grease Cutter

Safety Data Sheet

TOTAL
SOLUTIONS™

Personal protective equipment

: Use appropriate personal protective equipment when risk assessment indicates this is necessary.
Gloves. Safety glasses. Protective clothing.



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: clear. Blue liquid.
Odor	: slight detergent odor
Odor threshold	: No data available
pH	: 12.5 – 14
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 200 °F Closed Cup
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 1.09 g/ml
Solubility	: Soluble in water.
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
VOC content	: < 7 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Upon combustion: CO and CO₂ are formed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Refer to section 10.1 on Reactivity.

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

May be corrosive to metals. Strong acids.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Glycol Ether EB (111-76-2)	
LD50 oral rat	1300 mg/kg
LD50 dermal rat	> 2000 mg/kg

Grease Cutter

Safety Data Sheet

Glycol Ether EB (111-76-2)	
ATE CLP (oral)	1300.000 mg/kg body weight
ATE CLP (dermal)	1100.000 mg/kg body weight
ATE CLP (dust, mist)	1.500 mg/l/4h

potassium hydroxide (1310-58-3)	
LD50 oral rat	273 mg/kg (Rat)
ATE CLP (oral)	273.000 mg/kg body weight

2-aminoethanol, ethanolamine (141-43-5)	
LD50 oral rat	1720 mg/kg female
LD50 dermal rabbit	1000 mg/kg
ATE CLP (oral)	500.000 mg/kg body weight
ATE CLP (dermal)	1100.000 mg/kg body weight
ATE CLP (dust, mist)	1.500 mg/l/4h

sodium dodecylbenzenesulfonate (25155-30-0)	
LD50 oral rat	438 mg/kg (Rat)

Skin corrosion/irritation	: Causes severe skin burns and eye damage. pH: 12.5 - 14
Serious eye damage/irritation	: Not classified pH: 12.5 - 14
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Glycol Ether EB (111-76-2)	
IARC group	3 - Not classifiable

Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Not classified
Specific target organ toxicity – repeated exposure	: Not classified

Glycol Ether EB (111-76-2)	
NOAEL (oral,rat,90 days)	see comments
NOAEL (dermal,rat/rabbit,90 days)	see comments

Aspiration hazard	: Not classified
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Causes severe burns.
Symptoms/effects after eye contact	: Causes serious eye damage. Corrosion of the eye tissue. Permanent eye damage.
Symptoms/effects after ingestion	: Gastrointestinal complaints. Burns to the gastric/intestinal mucosa.
Likely routes of exposure	: Skin and eye contact

SECTION 12: Ecological information

12.1. Toxicity

Glycol Ether EB (111-76-2)	
LC50 fish 1	1474 mg/l Oncorhynchus mykiss
EC50 Daphnia 1	100 mg/l Water flea
ErC50 (algae)	1840 mg/l Pseudokirchneriella subcapitata
NOEC chronic fish	> 100 mg/l
NOEC chronic crustacea	100 mg/l daphnid
potassium hydroxide (1310-58-3)	
LC50 fish 2	80 mg/l (LC50; 96 h)
sodium dodecylbenzenesulfonate (25155-30-0)	
LC50 fish 1	0.99 mg/l (LC50; 96 h)
EC50 Daphnia 1	2.19 mg/l (EC50; 96 h)
Threshold limit algae 1	0.9 mg/l (EC50; 96 h)

12.2. Persistence and degradability

Grease Cutter

Safety Data Sheet

potassium hydroxide (1310-58-3)	
Persistence and degradability	Biodegradability: not applicable. No (test)data on mobility of the components available.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
sodium dodecylbenzenesulfonate (25155-30-0)	
Persistence and degradability	Readily biodegradable in water.

12.3. Bioaccumulative potential

potassium hydroxide (1310-58-3)	
Bioaccumulative potential	Not bioaccumulative.
sodium dodecylbenzenesulfonate (25155-30-0)	
BCF fish 1	286 (BCF)
BCF fish 2	130 (BCF)
Log Pow	0.45 - 1.96
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

Transport document description : UN1760 Corrosive liquids, n.o.s. (Potassium Hydroxide, Monoethanolamine), 8, III
 UN-No.(DOT) : UN1760
 Proper Shipping Name (DOT) : Corrosive liquids, n.o.s.
 Class (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136
 Hazard labels (DOT) : 8 - Corrosive



Packing group (DOT) : III - Minor Danger
 DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
 DOT Packaging Bulk (49 CFR 173.xxx) : 241
 DOT Symbols : G - Identifies PSN requiring a technical name
 DOT Special Provisions (49 CFR 172.102) : IB3,T7,TP1,TP28
 DOT Packaging Exceptions (49 CFR 173.xxx) : 154
 DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L
 DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L
 DOT Vessel Stowage Location : A
 DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Additional information

Emergency Response Guide (ERG) Number : 154
 Other information : This product may be eligible to be shipped as a Limited Quantity or Consumer Commodity ORM-D utilizing the exception found at 49 CFR 173.154.

ADR

No additional information available

Transport by sea

No additional information available

Grease Cutter

Safety Data Sheet

TOTAL
SOLUTIONS™**Air transport**

No additional information available

SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Glycol Ether EB	CAS No 111-76-2	3-7%
potassium hydroxide (1310-58-3)		
Not subject to reporting requirements of the United States SARA Section 313		
CERCLA RQ	1000 lb	
Sodium Tripolyphosphate Anhydrous (7758-29-4)		
Not subject to reporting requirements of the United States SARA Section 313		
CERCLA RQ	5000 lb	
sodium dodecylbenzenesulfonate (25155-30-0)		
Not subject to reporting requirements of the United States SARA Section 313		
CERCLA RQ	1000 lb	

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.


Full text of H-phrases:

H227	Combustible liquid
H290	May be corrosive to metals
H301	Toxic if swallowed
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard : 0 - Materials that will not burn under typical fire conditions, including intrinsically noncombustible materials such as concrete, stone, and sand.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.