

Aluminum Transmission & Engine Cleaner

Safety Data Sheet

TOTAL
SOLUTIONS™

SECTION 1: Product and company identification

Product name : Aluminum Transmission & Engine Cleaner
Use of the substance/mixture : Cleaner
Product code : 0663
Company : Total Solutions
P.O. Box 240014
Milwaukee, WI 53224 - USA
T (414) 354-6417
Emergency number : Chemtec: (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Skin Corr. 1C H314

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS05

Signal word (GHS-US) : Danger
Hazard statements (GHS-US) : Causes severe skin burns and eye damage
Precautionary statements (GHS-US) : Do not breathe dust
Wash thoroughly after handling
Wear eye protection, protective clothing, protective gloves
If swallowed: rinse mouth. Do NOT induce vomiting
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
If inhaled: Remove person to fresh air and keep comfortable for breathing
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
Immediately call a doctor, a POISON CENTER
Specific treatment (see First aid measures on this label)
Wash contaminated clothing before reuse
Store locked up
Dispose of contents/container to comply with local/regional/national/international regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

Full text of H-phrases: see section 16

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
sodium carbonate	(CAS No) 497-19-8	30-60	Eye Irrit. 2A, H319
disodium metasilicate	(CAS No) 6834-92-0	10-30	Skin Corr. 1B, H314 STOT SE 3, H335

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : If you feel unwell, seek medical advice (show the label where possible).

Aluminum Transmission & Engine Cleaner

Safety Data Sheet

TOTAL
SOLUTIONS™

First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: Take off immediately all contaminated clothing and wash it before reuse. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: Causes severe skin burns and eye damage.
Symptoms/injuries after inhalation	: May cause respiratory irritation.
Symptoms/injuries after skin contact	: Caustic burns/corrosion of the skin.
Symptoms/injuries after eye contact	: Causes serious eye damage. Corrosion of the eye tissue. Permanent eye damage.
Symptoms/injuries after ingestion	: Harmful if swallowed. Gastrointestinal complaints. Burns to the gastric/intestinal mucosa.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: All extinguishing media allowed.
------------------------------	------------------------------------

5.2. Special hazards arising from the substance or mixture

Reactivity	: Powder may produce chlorine gas when wet. Upon combustion: CO and CO ₂ are formed. If the product is involved in a fire, it can release toxic chlorine gases.
------------	--

5.3. Advice for firefighters

Firefighting instructions	: Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers. Take account of environmentally hazardous firefighting water.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Isolate from fire, if possible, without unnecessary risk.
------------------	---

6.1.1. For non-emergency personnel

Protective equipment	: Protective goggles. Gloves. Protective clothing.
Emergency procedures	: Evacuate unnecessary personnel. Avoid contact with skin, eyes and clothing. Ventilate spillage area.

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Stop leak if safe to do so. Stop release. Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent soil and water pollution.

6.3. Methods and material for containment and cleaning up

For containment	: Contain released substance, pump into suitable containers.
Methods for cleaning up	: Absorb spillage to prevent material damage. This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Comply with the legal requirements. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Do not get in eyes, on skin, or on clothing. Handle and open the container with care.
Hygiene measures	: Wash thoroughly after handling. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Comply with applicable regulations.
Storage conditions	: Store in corrosive resistant container with a resistant inner liner. Keep container closed when not in use.
Incompatible products	: acids. reducing agents.
Storage area	: Keep only in the original container. Store in a dry area. Store in a cool area.
Special rules on packaging	: meet the legal requirements. Keep only in original container.

Aluminum Transmission & Engine Cleaner

Safety Data Sheet

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

Personal protective equipment : Use appropriate personal protective equipment when risk assessment indicates this is necessary.
Safety glasses. Gloves. Protective clothing.



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Fine white powder.
Odor	: chlorine-like
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 200 °F Closed Cup
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: NA
Relative vapor density at 20 °C	: No data available
Solubility	: Soluble in water.
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
VOC content	: 0 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Powder may produce chlorine gas when wet. Upon combustion: CO and CO₂ are formed. If the product is involved in a fire, it can release toxic chlorine gases.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Refer to section 10.1 on Reactivity.

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

No additional information available

Aluminum Transmission & Engine Cleaner

Safety Data Sheet



10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

sodium carbonate (497-19-8)	
LD50 oral rat	2800 mg/kg (Rat; Experimental value)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit; Experimental value)
ATE CLP (oral)	2800.000 mg/kg body weight

Skin corrosion/irritation : Causes severe skin burns and eye damage.

Serious eye damage/irritation : Not classified

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

Symptoms/injuries after inhalation : May cause respiratory irritation.

Symptoms/injuries after skin contact : Caustic burns/corrosion of the skin.

Symptoms/injuries after eye contact : Causes serious eye damage. Corrosion of the eye tissue. Permanent eye damage.

Symptoms/injuries after ingestion : Harmful if swallowed. Gastrointestinal complaints. Burns to the gastric/intestinal mucosa.

SECTION 12: Ecological information

12.1. Toxicity

sodium carbonate (497-19-8)	
LC50 fish 1	300 mg/l (96 h; Lepomis macrochirus)
EC50 Daphnia 1	< 424 mg/l (48 h; Daphnia magna)
EC50 other aquatic organisms 1	14 mg/l (168 h; Plankton)
LC50 fish 2	740 mg/l (96 h; Gambusia affinis)
EC50 Daphnia 2	265 mg/l (48 h; Daphnia magna)
TLM fish 1	300 ppm (96 h; Lepomis macrochirus)
TLM other aquatic organisms 1	500 ppm (96 h; Daphnia magna)
Threshold limit algae 1	242 mg/l (5 days; Algae)

12.2. Persistence and degradability

sodium carbonate (497-19-8)	
Persistence and degradability	Biodegradability: not applicable. Low potential for adsorption in soil.
ThOD	Not applicable (inorganic)

12.3. Bioaccumulative potential

sodium carbonate (497-19-8)	
Log Pow	-6.19 (Estimated value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

Transport document description : UN3262 Corrosive solid, basic, inorganic, n.o.s., 8, III

UN-No.(DOT) : UN3262

Aluminum Transmission & Engine Cleaner

Safety Data Sheet

TOTAL
SOLUTIONS™

Proper Shipping Name (DOT) : Corrosive solid, basic, inorganic, n.o.s.
Transport hazard class(es) (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136
Hazard labels (DOT) : 8 - Corrosive



Packing group (DOT) : III - Minor Danger
DOT Packaging Non Bulk (49 CFR 173.xxx) : 213
DOT Packaging Bulk (49 CFR 173.xxx) : 240
DOT Symbols : G - Identifies PSN requiring a technical name
DOT Special Provisions (49 CFR 172.102) : IB8,IP3,T1,TP33
DOT Packaging Exceptions (49 CFR 173.xxx) : 154
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 25 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 100 kg
DOT Vessel Stowage Location : A
DOT Vessel Stowage Other : 52 - Stow "separated from" acids

Additional information

Other information : No supplementary information available.

ADR

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

Full text of H-phrases:


Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Corr. 1C	Skin corrosion/irritation Category 1C
H314	Causes severe skin burns and eye damage
H319	Causes serious eye irritation
H335	May cause respiratory irritation

Aluminum Transmission & Engine Cleaner

Safety Data Sheet

TOTAL
SOLUTIONS™

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.
NFPA fire hazard : 0 - Materials that will not burn.
NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.