



DESCRIPTION

A non-corrosive synthetic concentrate that produces a long lasting dense foam. It offers superior water retention as it effectively smothers and cools vapors. It is designed for use with fresh, sea and brackish water on Class A and Class B fires.

Do not breathe mist, spray. Wash thoroughly after handling. Wear eye protection, protective clothing, protective gloves.

IF ON SKIN: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. **If skin irritation occurs:** Get medical advice/attention. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. **If eye irritation persists:** Get medical advice/attention. Get medical advice/attention if you feel unwell.

WARNING: This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

DISPOSAL

Dispose of contents/container to comply with local/regional/national/international regulations.

*For industrial and commercial use only.
For additional information, see Safety Data Sheet.*

TOTAL SOLUTIONS®

SPECIALTY PRODUCTS

FIRE FIGHTING FOAM

For Use at 3% Dilution

- SUPERIOR WATER RETENTION,
SMOTHERING AND COOLING,
VAPOR SUPPRESSION

WARNING

Causes skin irritation.

Causes serious eye irritation.

May cause damage to organs through prolonged or repeated exposure.

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: One Gallon (128 fl. oz.)

Manufactured By: Total Solutions®
PO Box 240014 • Milwaukee, WI 53224 • 1-800-743-6417

DIRECTIONS

For use on Class A and Class B fires involving non-polar liquids, such as gasoline, fuel oil, benzene, mineral spirits and other hydrocarbons, dilute this concentrate to 3% using standard eductors or other proportioning system. May also be stored premixed at the correct solution.

This fire foam concentrate is compatible with surfactants and tank protectors. Do not mix with alcohol or any other antifreeze. Store at temperatures above 35°F.

NFPA® RATINGS

Health: 1; Flammability: 0; Reactivity: 0

CONTAINS/CAS NUMBER:

Water/7732-18-5; Sodium (C14-16) olefin sulfonate/68439-57-6; Diethylene glycol monobutyl ether/112-34-5; Ethylene glycol/107-21-1; Cocamidopropyl hydroxysultaine/68139-30-0; Linear alcohol/75782-86-4



Please Recycle.

0697.040617