

**FLOOR CARE TIPS:**

- Do not use your stripping or rinsing mop or bucket for the application of floor sealers. Always start with a clean, previously wrung-out cotton/rayon mop and bucket. Save this mop and bucket just for the application of sealer.
- To avoid the accumulations of finish build-up in corners or on baseboards, always the first coat of sealer no closer than 12 inches from baseboards. Apply second and every other coat up to baseboards.
- Always apply even, medium coats. To ensure the application of medium coats, wring out the bottom half of a fully saturated mop.
- Discard unused finish. Pouring unused finish from your bucket back into the original container can spoil the good finish. Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Do not breathe mist, spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear eye protection, protective clothing, protective gloves.

IF SWALLOWED: Rinse mouth. Call a doctor, a POISON CENTER if you feel unwell.

If exposed or concerned: Get medical advice/attention.

Store locked up.

*For industrial and commercial use only.
For additional information, see Safety Data Sheet.*

TOTAL SOLUTIONS®

RESILIENT FLOOR CARE

DIAMOND

Floor Sealer For Terrazzo

- WATER-BASED URETHANE-FORTIFIED FLOOR SEALER
- IDEAL FOR TERRAZZO AND POROUS STONE FLOORING
- SUPERIOR BASE COAT FOR ACRYLIC FINISHES SUBJECTED TO BURNISHING AND SPRAY BUFFING

WARNING

Harmful if swallowed. May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: One Gallon (128 fl. oz.)

Manufactured By: Total Solutions®
PO Box 240014 • Milwaukee, WI 53224 • 1-800-743-6417

DIRECTIONS

FOR CLEANING & DEODORIZING: Dilute 1 part with 25 parts water.

FOR PARTS WASHERS: Use product undiluted through parts washer system.

TO REMOVE GUM, WAX, ADHESIVES: Spray onto surface and allow a few minutes to work.

Spot check on an inconspicuous area first.

To prepare concrete floors: To prepare concrete floors prior to sealing, spray onto wet floor, allow to work for several minutes, then pick-up with an auto scrubber.

NFPA® RATINGS

Health: 2; Flammability: 2; Reactivity: 0

CONTAINS/CAS NUMBER:

Methyl Ester of Soybean Oil/67784-80-9; d-Limonene/5989-27-5; Polyethylene Glycol Octylphenyl Ether/9036-19-5; Nonylphenol Polyethoxylate/9016-45-9; Poly (Ethylene Oxide)/25322-68-3



Please Recycle.

1720.040315