

Technical Data Report

DYNAMITE BUTYL CLEANER



DESCRIPTION

DYNAMITE is a USDA authorized heavy duty cleaner. Can be diluted up to 40:1 with water. Use for general purpose cleaning. Removes dirt, grease, oil, and most other soils quickly and easily. Can be used in steam cleaners, warm or cold water and rotary machines. Also used for cleaning carpets, walls and industrial machinery. Contains solvents, detergents, emulsifiers, wetting agents, sequestering agents, penetrants and corrosion inhibitors.

APPLICATIONS

Use to clean grease, grime, oil, soot, food, dirt, mud, ink, carbon and lipstick. Areas of use include restaurants, hotels/motels, apartments, industrial plants, offices, schools, drilling rigs and stores.

FEATURES & BENEFITS

- Powerful formula removes even the toughest soils
- Safe to use on painted surfaces, metals and other inanimate objects—contains no caustics, acids or abrasives
- Rinses completely and quickly from all surfaces

SPECIFICATIONS

FORM: Liquid
ODOR: Mild Sweet
COLOR: Red
DETERGENCY: Strong
TOXICITY: 25 ppm OSHA TLV
WETTING ABILITY: Excellent
STORAGE STABILITY: 1 Year +
COLD STABILITY: 32°F
PHOSPHATES: <3%

FLASH POINT: None
BOILING POINT: 212°F +
SOLUBILITY IN WATER: 100%
SPECIFIC GRAVITY: 1.10
% VOLATILE BY VOLUME: 90%
pH: 13.3
VISCOSITY: Thin
EVAPORATION RATE: Slow
BIODEGRADABILITY: Yes

LABEL INFORMATION

DYNAMITE BUTYL CLEANER

This product is a concentrated industrial cleaner. For use on walls, carpet, floors, vinyl upholstery, metal surfaces, machinery, counter tops. Removes grease, oil, tar, wax, carbon, soot, smoke, ink, lipstick, food stains and heavy grime.

DIRECTIONS:

GENERAL PURPOSE CLEANING: Dilute up to 1:40. Use as outlined below for specific cleaning jobs.

WALLS: Mix 1:12 and spray, holding sponge underneath to prevent solution from running down and leaving clean streaks. On large areas clean from bottom up.

SHAMPOO: Mix 1:12 with warm water and use in dry foam or rotary shampoo machine. Do not overwet carpet.

WAX REMOVAL: Mix 1:16 with hot water. Apply to floor generously. Wait 10 minutes, then scrub with nylon pad.

VINYL UPHOLSTERY: Mix 1:8 with warm water. Spray. Wait 30 seconds. Wipe with sponge.

DEGREASING: Mix 1:9 and apply to motors or machinery. Allow to penetrate 3–4 minutes. Wash with hose or power sprayer.


DISCOLORED PAINT ON CARS AND TRUCKS: Mix 1:16 with warm water. Spray on. Wait 10 seconds. Wipe clean.

DANGER: Causes severe skin burns and eye damage. May be corrosive to metals.

Do not breathe mists. Wash hands thoroughly after handling. Wear protective gloves, eye protection and protective clothing. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center or doctor. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations. Keep only in original container. Absorb spillage to prevent material damage. Store in a corrosive resistant container with a resistant inner liner.

CONTAINS (CAS #): Water (7732-18-5), 2-Butoxy Ethanol (111-76-2), Sodium metasilicate pentahydrate (10213-79-3), Phosphate ester (N/A), Sodium hydroxide (1310-73-2).

HEALTH	2
FLAMMABILITY	0
REACTIVITY	0
PERSONAL	B



PACKAGING INFORMATION

Available in 4x1 gallons, 5 and 6 gallon pails, and 55 gallon drums.