



DESCRIPTION

This premium light lubricating oil is specially formulated for multi-purpose use by all municipal, industrial and institutional maintenance personnel. This labor saving product is indispensable for all mechanics, machinists, tool makers, pipefitters, assemblers and installers, plumbers and for all other maintenance functions.

- Saves production, maintenance and repair time.
- Protects and preserves valuable tools and equipment.
- Seals out moisture on mechanical and electrical equipment.
- Lubricates precision equipment. •Protects against corrosion.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, open flames, sparks. - No smoking. Wear eye protection, protective clothing, protective gloves.

IF SWALLOWED: Immediately call a doctor, a POISON CENTER. Do NOT induce vomiting. **If exposed or concerned:** Get medical advice/attention.

In case of fire: Use carbon dioxide (CO₂), dry extinguishing powder, foam to extinguish.

Store in a well-ventilated place. Keep cool. Store locked up.

DISPOSAL: Dispose of contents/container to comply with local/regional/national/international regulations.

*For industrial and commercial use only.
For additional information, see Safety Data Sheet.*

TOTAL SOLUTIONS®

SPECIALTY PRODUCTS

MULTI-PURPOSE PENETRANT

Displaces and Seals Out
Moisture to Prevent Rust

- PENETRATES THREADS, CRACKS,
AND JOINTS
- LUBRICATES METAL SURFACES

DANGER

Combustible liquid.

May be fatal if swallowed and enters airways.

May cause cancer.

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: One Gallon (128 fl. oz.)

Manufactured By: Total Solutions®
PO Box 240014 • Milwaukee, WI 53224 • 1-800-743-6417

DIRECTIONS

Generously apply this oil to all surfaces requiring protection by brushing, spraying, swabbing or dipping. Re-apply as needed when lubricating film is worn or weathered off.

NFPA® RATINGS

Health: 2; Flammability: 2; Reactivity: 0

CONTAINS/CAS NUMBER: Distillates, Petroleum, Hydrotreated Light/64742-47-8;
Alkanes, C14-16/90622-46-1; Proprietary/Mixture; Aliphatic Hydrocarbon/8052-41-3;
Mineral Oil/64742-52-5



Please Recycle.

0300.031417