

QuestSpecialty

MC-FREE DRY MOLY

Methylene Chloride-Free Dry Film Lubricant

Lubricante de Capa Seca sin Cloruro de Metileno

Fast Drying • Waterproof • Retards Rust
Temperature Range -40°F to 662°F
Contains No Grease or Oil

Non-conductive, Non-corrosive & Non-chlorinated
Non-flammable When Dry
Resists Pressures Up To 250,000 psi

DANGER/PELIGRO:
EXTREMELY FLAMMABLE AEROSOL. CONTAINS GAS
UNDER PRESSURE; MAY EXPLODE IF HEATED.
AEROSOL. EXTREMADAMENTE INFLAMABLE. CONTIENE
GAS A PRESIÓN; PUEDE EXPLOTAR SI SE CALIENTA.

NET WT. 11 OZ. (312 g)

QuestSpecialty Corporation
P.O. Box 624 • Brenham, TX 77834
713.896.8188

MC-FREE DRY MOLY

Methylene Chloride-Free
Dry Film Lubricant

- Cleaner application
- Resists dust and abrasive particles
- Withstands water, oils, alkalis and most acids
- Will not wipe off easily—chemically attracted to metal
- Permits immediate use of chain or gear after application
- Will not run off part to which applied, requires less frequent lubrication
- Can be used at higher temperatures and will not carbonize
- Replaces graphite

RECOMMENDED FOR: Foundries; machine shops; automotive plants; vehicle maintenance; sewing trades; paper and corrugated converting; chemical plants; marine, oil field, and mining operations; etc.

FOR USE ON: Oil drilling equipment, pipe threads, lathe bed and rails, chains and sprockets, road equipment, door locks and hinges, etc. Also may be used as a release agent.

DIRECTIONS: Shake container well before using. Clean surface thoroughly. Apply a thin, even film by spraying or brushing. Thick coats decrease efficiency. Dries in 1 to 3 minutes. Allow to cure 30 minutes before exposing to water.

INSTRUCCIONES: Agite bien antes de usar. Limpie bien la superficie. Aplique una capa delgada, rociando o alpicando con una brocha. Se recomienda que sean capas pequeñas. Se seca en 1 a 3 minutos. Permita que se seque 30 minutos antes de exponer a agua.

DANGER: Extremely Flammable Aerosol. Contains gas under pressure; may explode if heated. Causes skin and serious eye irritation. May damage fertility or the unborn child.

Keep away from heat, sparks, open flames, and hot surfaces. —No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves and eye protection. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing. If eye irritation persists: Get medical attention. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. If exposed or concerned: Get medical advice or attention. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations.

PELIGRO: Aerosol. Extremadamente inflamable. Contiene gas a presión; Puede explotar si se calienta. Causa irritación de la piel y ocular. Puede perjudicar la fertilidad o el feto. Mantenga lejos de calor, chispas, llamas abiertas, y superficies calientes. —No fumar. No pulverice en llamas abiertas u otra fuente de ignición. Envase presurizado: No perforo ni queme, incluso después de usar. Proteja de la luz solar. No exponga a temperaturas que excedan 50°C/122°F. Almacene en un lugar bien ventilado. Lávese bien las manos después de manipular. Use guantes protectores y protección para los ojos. Si en la piel: Lave con bastante agua. Si irritación en la piel ocurre: Obtenga atención médica. Remueva la ropa contaminada lávela antes de utilizar. Si cae en los ojos; Enjuague cuidadosamente con agua durante varios minutos. Remueva lentes de contacto, si están presentes y fáciles de remover. Continúe enjuagando. Si persiste la irritación ocular: Consulte con un médico. Obtenga instrucciones especiales antes de utilizar. No manipule antes de haber leído y comprendido todas las precauciones de seguridad. Si ha sido expuesto o preocupado: Obtenga atención médica. Almacene bajo llaves. Elimine el contenido y envase de acuerdo con las ordenanzas locales, estatales, y reglamentos nacionales.

Contains (CAS#): Acetone (67-64-1), Propane/n-Butane (58476-86-8), Isopropyl Alcohol (67-63-0), Molybdenum Disulfide (1317-33-5), Toluene (108-88-3).

HMIS RATINGS: Health - 2, Flammability - 3, Reactivity - 0, Personal - B.

ITEM 521000001-160Z Made in USA

