

Technical Data Report

SILI LUBE

HEAVY DUTY SILICONE SPRAY



DESCRIPTION

SILI LUBE is a multi-purpose silicone spray. Non-flammable formula is safe to use in plant areas. Formula uses a high viscosity silicone for long lasting lubrication and protection. Non-conductive to 28,000 volts. Stable temperatures up to 400°F.

APPLICATIONS

Cleans, shines and leaves a protective film on rusted parts, wire cable, door hinges, chains, hoists, pulleys, cranes, fork lifts, sprockets, gears, block and tackle, conveyors, construction machinery, industrial parts and locks. Areas of use include farms, oil rigs and refineries, bottling plants, dairies, paper mills, cotton gins, air conditioning, industrial plants, textile plants, lumber mills, cement plants and automotive/motorcycle/marine repair.

FEATURES & BENEFITS

- Reduces metal-to-metal noises and rubber-to-metal squeaks
- Clean, non-staining formula
- Waterproof and rustproof
- Non-flammable

SPECIFICATIONS

FORM: Solvent-Based Aerosol
ODOR: Chlorinated Solvent
COLOR: Clear
DETERGENCY: None
TOXICITY: 25 ppm OSHA TLV
WETTING ABILITY: Saturates
STORAGE STABILITY: 1 Year +
COLD STABILITY: 0°F
PHOSPHATES: None

FLASH POINT: None
FLAME EXTENSION: None
SOLUBILITY IN WATER: 0%
SPECIFIC GRAVITY: 1.46
% VOLATILE BY VOLUME: 95%
pH: N/A
PROPELLANT: Carbon Dioxide
EVAPORATION RATE: Slow
BIODEGRADABILITY: No

LABEL INFORMATION

SILI LUBE SILICONE SPRAY

Stops sticking of drawers, windows, doors, screens, zippers and locks. Eliminates annoying squeaks in hinges, latches and springs, etc. Stops car doors, locks and trunk moldings from sticking.

Retards corrosion – protects battery terminals, tools, guns, skates, aluminum windows and doors, etc. Waterproofs ignition systems and sparkplugs. Prevents jamming and production slow down. Contains no animal or vegetable fats. Absolutely neutral.

DIRECTIONS: Thoroughly clean the surface to be sprayed. Spray a light film with a sweep motion. When used on sticking surfaces, work object back and forth. Spray again if necessary.

NOTE: Product may harm some plastics TEST before using.


DANGER: Contains gas under pressure; may explode if heated. Causes skin and serious eye irritation. May cause cancer. May cause drowsiness or dizziness. Suspected of causing genetic defects.

Keep away from heat, sparks, open flames, and hot surfaces. –No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves, eye protection and protective clothing. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. If exposed or concerned: Get medical attention. Avoid breathing fumes, mist, vapors, and spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell.

Warning: This product contains chemical(s) known to the State of California to cause cancer.

CONTAINS (CAS#): Trichloroethylene (79-01-6), Tetrachloroethylene (127-18-4), Polysiloxane (63148-62-9), Carbon Dioxide (124-38-9).

HEALTH	2
FLAMMABILITY	0
REACTIVITY	1
PERSONAL	C



PACKAGING INFORMATION

12 – 16 oz. cans per case, 15 oz. net weight