



Product # 5760

Technical Data Report

NUCHAIN

CHAIN & CABLE LUBRICANT WITH MOLY



DESCRIPTION

NUCHAIN is specially designed to provide maximum protection to wire ropes and chains of all types. Will completely penetrate into the strands of wire ropes, providing the ultimate in lubrication. Does not build up on chains to attract dust or dirt, but provides complete lubrication of rollers, pins and bushings. Continued use of this product reduces chain whip, vibration and noise; also protects against galling, seizing and wear, thus adds life to chain cable and sprockets.

APPLICATIONS

Used for loosening rusted parts and lubrication of wire cable, door hinges, chains, hoists, pulleys, cranes, fork lifts, sprockets, gears, blocks and tackle, conveyors, construction machinery, industrial parts and locks. Areas of use include farms, oil rigs and refineries, bottling plants, dairies, paper mills, cotton gins, air conditioning, industrial plants, textile plants, lumber mills, cement plants and automotive/motorcycle/marine repair.

FEATURES & BENEFITS

- Prolongs life of chains, cables and wire ropes
- Will not attract dust and dirt
- Protects against galling, seizing, and wear
- Prolonged use reduces chain whip, vibration, and noise

SPECIFICATIONS

FORM: Oil Based Aerosol
ODOR: Mild Solvent
COLOR: Gray-Black
DETERGENCY: None
TOXICITY: 200 ppm OSHA TLV
WETTING ABILITY: Saturates
STORAGE STABILITY: 1 Year +
COLD STABILITY: 0°F
PHOSPHATES: None

FLASH POINT: N/A
FLAME EXTENSION: 18" +
SOLUBILITY IN WATER: 0%
SPECIFIC GRAVITY: 0.92
% VOLATILE BY VOLUME: 99%
pH: N/A
PROPELLANT: Hydrocarbon
EVAPORATION RATE: N/A
BIODEGRADABILITY: No

LABEL INFORMATION

NUCHAIN CHAIN & CABLE LUBRICANT WITH MOLY


This high speed chain and cable lubricant with moly is specially designed to provide maximum protection to wire ropes and chains of all types. This product will completely penetrate into the strands of wire ropes providing the ultimate in lubrication. This product will not build up on chains to attract dust or dirt, but will provide complete lubrication on rollers, pins and bushings. Continued use of this product reduces chain whip, vibration and noise, also protects against galling, seizing and wear, thus adds life to chain cable and sprockets.

DIRECTIONS: Shake well. Surface to be sprayed should be clean and dry. Remove protective cap. Hold container 6-12 inches from surface to be treated. Point opening in desired direction. Press button to spray.

DANGER: Extremely Flammable Aerosol. Contains gas under pressure: May explode if heated. Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Warning: This product contains chemicals known to the State of California to cause cancer.

CONTAINS (CAS#): Heavy Naphthenic Petroleum Distillate (64742-52-5), Propane/n-Butane (68476-86-8), Stoddard Solvent (8052-41-3).

HEALTH	1
FLAMMABILITY	2
REACTIVITY	0
PERSONAL	A



PACKAGING INFORMATION

12 – 16 oz cans per case, 12.5 oz net weight