

QuestSpecialty

FUSION
AP

Misting
Spray Adhesive

FUSION
AP

Misting Spray Adhesive

Adhesivo de Rocío de Niebla

All Purpose Misting Spray
Quick Adhesion & Tacking
Permanent or Temporary Bonds
BONDS: Labels, Cartons, Cloth,
Plastic, Polyethylene Sheeting,
Foam, Ceramic, Glass, Wood,
Formica & More

DANGER/PELIGRO:
EXTREMELY FLAMMABLE AEROSOL. CONTAINS
GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.
AEROSOL EXTREMADAMENTE INFLAMABLE. CONTIENE
GAS A PRESIÓN; PUEDE EXPLOTAR SI SE CALIENTA.

NET WT. 12 OZ. (340 g)

QuestSpecialty Corporation
P.O. Box 624 • Brenham, TX 77834
713.896.8188

This misting pressure sensitive spray adhesive is designed to create both permanent and temporary bonds on a wide range of surfaces. Excellent for porous or uneven surfaces as well as smooth surfaces. Waterproof, flexible, transparent, non-staining adhesive sets quickly. Effectively bonds such surfaces as labels, cartons, cloth, plastic, ceramic, glass, wood, Formica®, leather, foam, polyethylene sheeting, etc. Cleans up with mineral spirits.

DIRECTIONS FOR USE: Shake well before using. Remove cap. Point opening in desired direction. Hold container 8-12 inches from surface to be sprayed. Press button to spray. For best results, apply adhesive using side to side spraying motion. **FOR TEMPORARY BONDS:** Apply to surface, allow to tack and apply material to be bonded. **FOR PERMANENT BONDS:** Apply to both surfaces to be joined. Allow to tack and then press surfaces together. After use, invert can and spray until tip is clear to prevent clogging. If adhesive accumulates around opening in spray nozzle, wipe clear while wet. If opening becomes clogged, remove with degreasing solvent.

MODO DE EMPLEO: Agite bien antes de usar. Remueva la tapa. Apunte la abertura en la dirección deseada. Sostenga el contenedor de 8 a 12 pulgadas de la superficie que se va rociar. Para mejores resultados, rocíe el adhesivo de lado a lado. **PARA PEGAR TEMPORALMENTE,** rocíe la superficie, permita que se vuelva pegajoso y después ponga el material que se va a pegar. **PARA PEGAR PERMANENTEMENTE,** rocíe las superficies que se van a pegar y presiónelas. Después de usar, ponga el bote boca abajo y oprima la boquilla hasta que el rocío salga claro para prevenir que se tape. Si el adhesivo se acumula alrededor de la boquilla, límpiela mientras esté húmeda. Si la abertura se tapa, remuévala con solvente desengrasante.

DANGER: Extremely Flammable Aerosol. Contains gas under pressure, may explode if heated. Causes skin and serious eye irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to Central nervous system through prolonged or repeated exposure. May be fatal if swallowed and enters airways. Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves and eye protection. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. If exposed or concerned: Get medical advice or attention. Do not breathe fumes, mist, vapors, and spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh

air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Dispose of contents and container in accordance with local, state, and national regulations.



PELIGRO: Aerosol Extremadamente Inflamable. Contiene gas a presión; puede explotar si se calienta. Causa irritación de la piel y los ojos grave. Se sospecha que perjudica la fertilidad o el feto. Puede causar somnolencia o mareos. Puede causar daños al sistema nervioso central través de la exposición prolongada o repetida. Puede ser fatal en caso de ingestión y entra por las vías respiratorias. Mantenga lejos de calor, chispas, llamas abiertas, y superficies calientes. -No fumar. No pulverice en llamas abiertas u otra fuente de ignición. Envase presurizado: No perforar ni quemar, incluso después de usar. Proteja de la luz solar. No exponga a temperaturas que excedan 50°C/122°F. Almacene en un lugar bien-ventilado. Lávese bien las manos después de manipular. Use guantes protectores y protección para los ojos. Si en la piel: Lave con bastante agua. Si irritación en la piel ocurre: Obtenga atención médica. Remueva la ropa contaminada lávela antes de utilizar. Si cae en los ojos: Enjuague cuidadosamente con agua durante varios minutos. Remueva lentes de contacto, si están presentes y fáciles de remover. Continúe enjuagando. Si persiste la irritación ocular: Consulte con un médico. Obtenga instrucciones especiales antes de utilizar. No manipule antes de haber leído y comprendido todas las precauciones de seguridad. Si ha sido expuesto o preocupado: Obtenga atención médica. No respirar el humo, niebla, vapores y rocío. Utilice únicamente en el exterior o en un lugar bien ventilado. Si se inhala: Remueva la persona al aire fresco y mantenga cómoda para respirar. Llame al un centro de control de venenos o a un médico si se encuentra mal. Si se ingiere: Llame inmediatamente a un centro de control de venenos. NO induzca vomito. Elimine el contenido y envase de acuerdo con las ordenanzas locales, estatales, y reglamentos nacionales.

CONTAINS (CAS#): Acetone (67-64-1), Hexane (110-54-3), Methyl Acetate (79-20-9), Propane/n-Butane (68476-86-8).

HMS RATINGS: Health - 2, Flammability - 3, Reactivity - 0, Personal - B.

VOC Category: Web Spray Adhesive

VOC Limit: Meets the VOC Standard of 65% by weight.



ITEM 586000001-20AR

Made in USA

600005586