



Product # 5860

Technical Data Report

FUSION AP

MISTING SPRAY ADHESIVE



DESCRIPTION

FUSION AP is a misting pressure sensitive spray adhesive designed to be used on a wide range of surfaces. Creates both permanent and temporary bonds on many surfaces. Excellent for porous or uneven surfaces as well as smooth surfaces. Waterproof, flexible, transparent, non-staining adhesive sets quickly.

APPLICATIONS

Effectively bonds such surfaces as labels, cartons, cloth, plastic, ceramic, glass, wood, Formica®, leather, foam, polyethylene sheeting, etc. Cleans up with mineral spirits. Areas of use include printers, industrial plants, shipping departments, schools, construction areas, auto upholstery repair shops and furniture manufacturers.

FEATURES & BENEFITS

- All purpose misting spray
- Quick adhesion & tacking
- Permanent or temporary bonds
- BONDS: Labels, cartons, cloth, plastic, polyethylene sheeting, foam, ceramic, glass, wood, Formica® and more

SPECIFICATIONS

FORM: Solvent-Based Aerosol
ODOR: Solvent
COLOR: Milky White
DETERGENCY: None
TOXICITY: 300 ppm
WETTING ABILITY: None
STORAGE STABILITY: 1 Year +
COLD STABILITY: 0°F
PHOSPHATES: None

FLASH POINT: -2°F (-19°C)
FLAME EXTENSION: 18" +
SOLUBILITY IN WATER: Immiscible
SPECIFIC GRAVITY: 0.84
% VOC: 55.68%
pH: N/A
PROPELLANT: Hydrocarbon
EVAPORATION RATE: Medium
BIODEGRADABILITY: No

LABEL INFORMATION

FUSION AP MISTING SPRAY ADHESIVE

This misting pressure sensitive spray adhesive is designed to create both permanent and temporary bonds on a wide range of surfaces. Excellent for porous or uneven surfaces as well as smooth surfaces. Waterproof, flexible, transparent, non-staining adhesive sets quickly. Effectively bonds such surfaces as labels, cartons, cloth, plastic, ceramic, glass, wood, Formica®, leather, foam, polyethylene sheeting, etc. Cleans up with mineral spirits.

DIRECTIONS FOR USE: Shake well before using. Remove cap. Point opening in desired direction. Hold container 8-12 inches from surface to be sprayed. Press button to spray. For best results, apply adhesive using side to side spraying motion. For Temporary Bonds: Apply to surface, allow to tack and apply material to be bonded. For Permanent Bonds: Apply to both surfaces to be joined. Allow to tack and then press surfaces together. After use, invert can and spray until tip is clear to prevent clogging. If adhesive accumulates around opening in spray nozzle, wipe clear while wet. If opening becomes clogged, remove with degreasing solvent.

DANGER: Extremely Flammable Aerosol. Contains gas under pressure; may explode if heated. Causes skin and eye irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to Central nervous system through prolonged or repeated exposure. May be fatal if swallowed and enters airways.


Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves and eye protection. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. If exposed or concerned: Get medical advice or attention. Do not breathe fumes, mist, vapors, and spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Dispose of contents and container in accordance with local, state, and national regulations.

CONTAINS (CAS#): Acetone (67-64-1), Hexane (110-54-3), Methyl Acetate (79-20-9), Propane/n-Butane (68476-86-8).

VOC Category: Web Spray Adhesive

VOC Limit: Meets the VOC Standard of 65% by weight.

HEALTH	2
FLAMMABILITY	3
REACTIVITY	0
PERSONAL	B



PACKAGING INFORMATION

12 - 20 oz. cans per case, 12 oz. net weight