



Product # 6030

Technical Data Report

RUTHLESS

PAINT & VARNISH REMOVER



DESCRIPTION

RUTHLESS is a USDA authorized gel base paint remover. Penetrates deep to remove paint, decals, gaskets, glue, graffiti, and labels from most surfaces. Washes off with water or solvent. Safe to use on metal, brick, ceramic, wood and tile surfaces. Clings to all vertical surfaces. Contains a chemical seal to prevent evaporation of paint removing solvents. Non-flammable.

APPLICATIONS

For removal of paint, decals, epoxy, lacquer, gaskets, glue, carbon deposits, silicone, simulated wood paneling and other materials from metal, wood, brick, ceramic, and natural stone surfaces. Areas of use include auto dealerships, paint shops, factories, motels, hotels, schools, hospitals, homes and restaurants. NOTE: WILL DAMAGE PLASTICS.

FEATURES & BENEFITS

- Versatile, multipurpose product removes a broad range of materials from most surfaces
- Thick formula clings to vertical surfaces, increasing contact time
- Works quickly and efficiently

SPECIFICATIONS

FORM: Solvent-Based Liquid
ODOR: Strong Chlorinated Solvent
COLOR: Clear to Hazy
DETERGENCY: Strong
TOXICITY: 25 ppm OSHA PEL
WETTING ABILITY: Excellent
STORAGE STABILITY: 1 Year +
COLD STABILITY: 0°F
PHOSPHATES: None

FLASH POINT: N/A
BOILING POINT: 104°F
SOLUBILITY IN WATER: 17.00%
SPECIFIC GRAVITY: 1.185
% VOLATILE BY VOLUME: 97.3%
pH: N/A
VISCOSITY: Very Thick
EVAPORATION RATE: Fast
BIODEGRADABILITY: No

LABEL INFORMATION

RUTHLESS PAINT & VARNISH REMOVER

RUTHLESS is a USDA authorized gel base paint remover. Penetrates deep to remove paint, decals, gaskets, glue, graffiti, and labels from most surfaces. Washes off with water or solvent. Safe to use on metal, brick, ceramic, wood and tile surfaces. Clings to all vertical surfaces. Contains a chemical seal to prevent evaporation of paint removing solvents. Non-flammable.


DIRECTIONS FOR USE: PAINT STRIPPING: Preclean accumulations of dirt and grease with a heavy duty detergent. Allow to dry. Apply undiluted compound in a full heavy coat. Allow to stand until paint is thoroughly wrinkled or bubbled. Flush with water or solvent. Use a scraper or wire brush in cracks, crevices or on stubborn accumulation. On painted floors, a squeegee may be used to move the stripper from one area to another when finished, and compound may be reused. Add new product periodically. GASKET REMOVAL: Apply liberally to gasket and surrounding surfaces. Allow to stand for several minutes before removing gasket with scraper or wire brush. DECAL REMOVAL: Apply compound to decal. Allow to stand several minutes. Remove decal with scraper. Reapply if needed to remove adhesive residue. Rinse.

DANGER: Toxic if swallowed, in contact with skin, or if inhaled. Causes skin and serious eye irritation. Suspected of causing cancer. Causes damage to eyes or central nervous system with prolonged or repeated exposure. Store in a well-ventilated place. Wear protective gloves and eye protection. Wash hands thoroughly after handling. Do not eat, drink, or smoke when using this product. Do not breathe fumes, mist, vapors, or spray. Use only outdoors or in a well-ventilated area. If swallowed: Immediately call a poison center or doctor. Rinse mouth. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison control center or doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Take off immediately all contaminated clothing and wash it before reuse. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. If exposed or concerned: Get medical advice or attention.

WARNING: This product contains chemical(s) known to the State of California to cause cancer and birth defects or other reproductive harm.

CONTAINS (CAS#): Methylene chloride (75-09-2), Methanol (67-56-1), Paraffin (8002-74-2), Nonionic Surfactant (127087-87-0).

HEALTH	3
FLAMMABILITY	1
REACTIVITY	0
PERSONAL	B



PACKAGING INFORMATION

Available in 4 x 1 gallons, 5 and 6 gallon pails and 55 gallon drums.