



Finishing Touch

Foaming Tire Shine

Finishing Touch

Foaming Tire Shine

Espuma Lustradora De Llantas

Clinging Foam Cleans,
Shines, Protects

Long Lasting High Gloss Shine

Water Based — VOC Compliant

One Step Application

No Wiping Required

DANGER/PELIGRO:

**EXTREMELY FLAMMABLE AEROSOL. CONTAINS GAS
UNDER PRESSURE; MAY EXPLODE IF HEATED.**

AEROSOL EXTREMADAMENTE INFLAMABLE.

**CONTIENE GAS A PRESIÓN;
PUEDE EXPLOTAR SI SE CALIENTA.**

NET WT. 15 OZ. (425 g)

QuestSpecialty Corporation
P.O. Box 624 • Brenham, TX 77834
713.896.8188

This product quickly cleans tires without wiping or scrubbing. Once foam dissipates, a high gloss protective shine remains on the tire for days. Simply spray on and walk away. Quickly penetrates to lift grease, dirt, and grime from tire sidewalls. Thick clinging foam prevents runs and drips onto wheels. Each can will clean, shine, and protect up to 30 tires and will not harm wheels or wheel covers.

Ideally suited for use in a variety of areas including fleet shops, detail shops, car washes, bus barns, automotive dealers, automotive repair shops. For use on all car, truck, bus, and equipment tires.

DIRECTIONS FOR USE: This product should only be applied to tire sidewalls, not tire treads, brake pedals, or other areas where slippery conditions should be avoided. Not intended for use in auto body repair shops as it contains silicone. Shake well. Spray evenly over surface in a slow sweeping motion, keeping can 6-8 inches from tire surface. Allow foam to completely dissipate, about 10 minutes. Excessive brake dust should be removed prior to treatment. No wiping is required.

MODO DE EMPLEO: Este producto debe ser aplicado solamente en las paredes de las llantas, no en la suela, pedales de los frenos, o otras áreas que condiciones resbalosas debe ser evitadas. No esta intencionado para el uso en talleres de latoneria y pintura porque contiene silicón.

Agite bien. Rocíe la superficie en forma pareja con un movimiento de un lado a otro. Mantenga el bote de 6 a 8 pulgadas de la superficie de la llanta. Permita que la espuma se disipe por 10 minutos. El excesivo polvo de frenos debe ser removido antes de aplicar el tratamiento. No se requiere limpiar con un trapo.

DANGER: Extremely Flammable Aerosol. Contains gas under pressure; may explode if heated.


Keep away from heat, sparks, open flames, and hot surfaces. —No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place.

PELIGRO: Aerosol Extremadamente Inflamable. Contiene gas a presión; Puede explotar si se calienta.

Mantenga lejos de calor, chispas, llamas abiertas, y superficies calientes. —No Fumar. No pulverice en llamas abiertas u otra fuente de ignición. Envase presurizado: No perfore ni queme, incluso después de usar. Proteja de la luz solar. No exponga a temperaturas que excedan 50°C/122°F. Almacene en un lugar bien-ventilada.

CONTAINS (CAS#): Water (7732-18-5), Propane/n-Butane (68476-86-8), Glycerine (56-81-5), Dipropylene Glycol Monomethyl Ether (34590-94-8), Polydimethyl Siloxane (9016-00-6).

HEALTH	1
FLAMMABILITY	1
REACTIVITY	0
PERSONAL	A



ITEM 804000001-20AR

Made in USA

