

CUTTING & TAPPING FLUID

ANGER:

Extremely flammable aerosol. May cause cancer. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wear protective gloves/protective clothing/eye protection/face protection. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 49°C/120°F. Dispose of contents/container in accordance with local/regional/national/international regulations.

FIRST AID:

IF EXPOSED OR CONCERNED: Get medical advice/attention. **IF ON SKIN:** Wash off with warm water and soap. Get medical attention if irritation develops or persists. **IF IN EYES:** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops or persists. Continue rinsing. **IF INHALED:** If symptoms develop move victim to fresh air. Oxygen or artificial respiration if needed. Get medical attention if symptoms persist. **IF SWALLOWED:** Have victim rinse mouth thoroughly with water. Do not induce vomiting without medical advice.

CONTAINS/CAS NUMBER:

Mineral Oil (64742-54-7), Chlorinated Paraffin (63449-39-8), Heavy Naphthenic Distillate (64741-96-4) and Propane (74-98-6)

Distributed By: Total Solutions®

PO Box 240014 • Milwaukee, WI 53224 • 1-800-743-6417

See Safety Data Sheet for complete safety information. 24 HOUR MEDICAL EMERGENCY 1-866-836-8855 CONTAINS NO OZONE DEPLETING CHEMICALS!



TOTAL SOLUTIONS®

SPECIALTY PRODUCTS

CUTTING & TAPPING FLUID

Thread Cutting Compound
For Steel, Aluminum, Brass
and Copper Metals

- CLINGS TO VERTICAL SURFACES
- HELPS PRODUCE CLEAN SHARP THREADS TIME AFTER TIME
- REDUCES HEAT AND FRICTION TO EASE CUTTING AND INCREASE TOOL LIFE

KEEP OUT OF REACH OF CHILDREN

DANGER

EXTREMELY FLAMMABLE.

HARMFUL OR FATAL IF SWALLOWED.

CONTENTS UNDER PRESSURE.

Read carefully other cautions on back panel.

NET WT: 13 OZ (369 g)

Distributed By: Total Solutions®

PO Box 240014 • Milwaukee, WI 53224 • 1-800-743-6417

DESCRIPTION

Compatible with all manual and motor-driven threading equipment. An excellent thread cutting lubricant for use on all types of metal. Free of all chlorinated solvent, Excellent anti-weld properties.

For use in/on drilling, sawing, reaming, turning, gear cutters, conduit threading, pipe thread cutting and automatic screw machines.

DIRECTIONS

Shake can well before using. Apply a liberal coating on area to be threaded. Re-apply frequently on motor driven equipment.

Re-apply with manual equipment when increased threading force is required.

DO NOT USE ON ENERGIZED EQUIPMENT

Cautions: Use with adequate ventilation. Intentional misuse by concentrating and inhaling the product can be harmful or fatal.

KEEP OUT OF REACH OF CHILDREN.

HMIS® RATINGS:

HEALTH - *3, FLAMMABILITY - 4, PHYSICAL HAZARD- 0, PERSONAL PROTECTION - X.

*=Chronic HMIS Code 0=Minimal 1=Slight 2=Moderate 3=Serious 4=Severe