

QuestSpecialty

Mr.
Blue

Premium Lithium E.P. Grease

Mr.
Blue

Premium Lithium
E.P. Grease
Premium Grasa Litio E.P.

Resists Thinning or Hardening in
Medium Sized High Speed Bearings

Lithium Grease with
Oxidation Inhibitors & Extreme Pressure
Additives for a Wide Range of Uses

Protects Surfaces Against Corrosion

Operating Range of 0°F to 350°F

CAUTION/PRECAUCIÓN:
KEEP OUT OF REACH OF CHILDREN
SEE ADDITIONAL CAUTIONS ON BACK PANEL
NO SE DEJE AL ALCANCE DE LOS NIÑOS
VEA PRECAUCIONES ADICIONALES EN EL PANEL TRASERO

NET CONTENTS: 14 OZ. (397 g)

QuestSpecialty Corporation
PO Box 624 • Brenham, TX 77834 • 713.896.8188

A multi-use grease for hundreds of automotive, marine, industrial and agricultural applications. Does not dry out after use as some clay based greases do. Remains pumpable at low temperatures. Forms protective film, resisting rust and corrosion. Resists chemical breakdown and oxidation. This waterproof lubricant will not wash out. Suitable for medium sized high speed bearings.

USES: Ball bearings, roller bearings, couplings, mechanical linkages, pumps, universal joints, ball joints, fifth wheels, wheel bearings, chassis.

DIRECTIONS FOR USE: Pump in new grease until old grease comes out. Remove old grease if possible. For ball type grease fittings: Fill until old grease comes out. Clean exposed areas with degreaser to remove old grease. Pump in new grease.

MODO DE EMPLEO: Inyecte grasa nueva hasta que la grasa vieja salga. Remueva la grasa vieja si es posible. Para conexiones de tipo bola: Llene hasta que la grasa vieja salga. Limpie las áreas expuestas con desengrasante para remover la grasa vieja. Inyecte nueva grasa.

CAUTION: Keep out of reach of children. May cause irritation to eyes. Prolonged contact with skin may cause irritation. If ingested, may cause nausea, vomiting, and diarrhea. For eye contact, flush with water, see physician if oily film persists.

For skin, wash with soap and water. For ingestion of more than 8 ounces contact physician.

PRECAUCIÓN: No se deje al alcance de los niños. Puede causar irritación a los ojos. El contacto prolongado puede causar irritación de la piel. Si es ingerido, puede causar náusea, vomito y diarrea. Si hay contacto con los ojos, enjuague con agua, vea a un médico si la sensación aceitosa persiste. Si hay contacto con la piel, lave con agua y jabón. Para la ingestión de más de 8 onzas contacte al médico.

CONTAINS (CAS#): Naphthenic Oil (64742-52-5), Lithium 12-hydroxystearate (7620-77-1), Lithium stearate (4485-12-5), Elco 102 (68649-42-3), Lubrizol 7065 OPC (N/A).

NLGI GRADE: 2

HMS Ratings: Health - 1, Flammability - 1, Reactivity - 0, Personal - A.

Made in USA 600005052



ITEM L1050001-145G